

# CLEAN STRIP™ (J-1 LIGHT)

V.O.C. COMPLIANT FORM RELEASE FOR ALL TYPES OF CONCRETE FORMS

## PRODUCT DESCRIPTION

Clean Strip (J-1 Light) is petroleum based, V.O.C. compliant, chemically reactive concrete form release supplied ready to-use. Clean Strip (J-1 Light) works to ensure clean, positive release on plywood, fiberglass, aluminum, steel, and other concrete forming materials. This product acts as a barrier to the adhesion of concrete while minimizing surface dusting. Clean Strip (J-1 Light) prolongs the life of plywood forms, and acts to reduce rusting of steel forms. Properly applied, Clean Strip (J-1 Light) will not stain concrete or interfere with the adhesion of coatings.

## ADVANTAGES

- V.O.C. compliant: Federal EPA, OTC, LADCO, CARB & SCAQMD
- Chemically reactive
- Clean, positive release
- Minimizes surface dusting
- Non-staining

## APPLICATION

Surfaces to be treated should be reasonably clean and free of all water, dust and dirt or residues, which might transfer to the final concrete surface. Apply during dry weather with low-pressure spray, roller or brush. Apply uniformly to assure proper coverage. Wipe excess material from forms prior to form construction and concrete placement. **FOR BEST RESULTS APPLY TO FORMS BEFORE EACH USE.**

## V.O.C. CONTENT

Less than 250 g/l. Compliant with all US VOC regulations for Concrete Form Release agents including Federal EPA, OTC, LADCO, SCAQMD & CARB.

## APPROXIMATE COVERAGE RATES:

	FT <sup>2</sup> per Gallon	M <sup>2</sup> per Liter
Plywood	1000	24.5
Medium density plywood	1500	36.8
High-density plywood	1750	42.9
Plastic faced plywood	1750	42.9
Fiberglass	1750	42.9
Steel	1750	42.9
Aluminum	1750	42.9

Texture and absorption of forming material will dictate final coverage rate.

## PACKAGING

ITEM #	Size	Liter
309113	5 Gal. Pail	18.9
309114	55 Gal. Drum	208
309115	275 Gal Tote	1040

## LIMITATIONS

Not for use as a bondbreaker or concrete release agent for tilt up concrete construction. Requires recoating after each use. Do not apply onto reinforcing steel. **DO NOT OVER APPLY.** Over application could cause excessive surface dusting.

Shelf life is two years from date of manufacture.

## WARNING

- Use with adequate ventilation
- Keep out of reach of children
- Do not take internally
- In case of ingestion, CALL A PHYSICIAN immediately, do not induce vomiting

If splashed in eyes, flush thoroughly with water for a minimum of 15 minutes. CALL A PHYSICIAN immediately. May cause irritation to the skin. If brought into contact with the skin, wash thoroughly with soap and water. Seek medical attention if redness or soreness occurs. Avoid breathing vapors or mist. Keep away from heat, sparks, open flames and other possible sources of ignition. Reseal container after each use. Wear protective clothing, gloves and goggles. Safe disposal of rags is necessary to avoid possibility of spontaneous combustion. Read MSDS before using product.

## MANUFACTURER

Dayton Superior Corporation  
7777 Washington Village Dr., Ste. 130  
Dayton, OH 45459  
Customer Service: 888-977-9600  
Technical Services: 866-329-8724  
Website: [www.daytonsuperior.com](http://www.daytonsuperior.com)

Refer to [www.daytonsuperior.com](http://www.daytonsuperior.com) for latest Technical Data Sheet and MSDS  
7777 Washington Village Dr., Suite 130, Dayton OH 45459  
Customer Service: (888) 977-9600  
Technical Assistance: (866) 329-8724

8/05/09 • For Commercial/Industrial Use Only • Page 1 of 2

# CLEAN STRIP™ (J-1 LIGHT)

CONTINUED

## WARRANTY

Dayton Superior Corporation ("Dayton") warrants for 12 months from the date of manufacture or for the duration of the published product shelf life, whichever is less, that at the time of shipment by Dayton, the product is free of manufacturing defects and conforms to Dayton's product properties in force on the date of acceptance by Dayton of the order. Dayton shall only be liable under this warranty if the product has been applied, used, and stored in accordance with Dayton's instructions, especially surface preparation and installation, in force on the date of acceptance by Dayton of the order. The purchaser must examine the product when received and promptly notify Dayton in writing of any non-conformity before the product is used and no later than 30 days after such non-conformity is first discovered. If Dayton, in its sole discretion, determines that the product breached the above warranty, it will, in its sole discretion, replace the non-conforming product, refund the purchase price or issue a credit in the amount of the purchase price. This is the sole and exclusive remedy for breach of this warranty. Only a Dayton officer is authorized to modify this warranty. The information in this data sheet supersedes all other sales information received by the customer during the sales process. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM, TRADE OR OTHERWISE.

## LIMITATION OF LIABILITY

Dayton shall not be liable in contract or in tort (including, without limitation, negligence, strict liability or otherwise) for loss of sales, revenues or profits; cost of capital or funds; business interruption or cost of downtime, loss of use, damage to or loss of use of other property (real or personal); failure to realize expected savings; frustration of economic or business expectations; claims by third parties (other than for bodily injury), or economic losses of any kind; or for any special, incidental, indirect, consequential, punitive or exemplary damages arising in any way out of the performance of, or failure to perform, its obligations under any contract for sale of product, even if Dayton could foresee or has been advised of the possibility of such damages. The Parties expressly agree that these limitations on damages are allocations of risk constituting, in part, the consideration for this contract, and also that such limitations shall survive the determination of any court of competent jurisdiction that any remedy provided in these terms or available at law fails of its essential purpose.



Refer to [www.daytonsuperior.com](http://www.daytonsuperior.com) for latest Technical Data Sheet and MSDS  
7777 Washington Village Dr., Suite 130, Dayton OH 45459  
Customer Service: (888) 977-9600  
Technical Assistance: (866) 329-8724

8/05/09 • For Commercial/Industrial Use Only • Page 2 of 2