

STANDOFF®

Liquid Marble Cleaner

cleaner for polished & glazed masonry

OVERVIEW

Stand Off® Liquid Marble Cleaner is a non-acidic, low odor, blue-colored gel manufactured for the commercial cleaning, restoration and maintenance of polished stonework or glazed masonry. Liquid Marble Cleaner loosens and dissolves surface dirt, carbon buildup and other atmospheric stains, allowing them to be washed away with a simple water rinse.

SPECIFICATIONS

For all PROSOCO product specifications visit www.prosoco.com and click on "SpecBuilder" or "Solution Finder."

ADVANTAGES

- An effective, non-acidic restoration cleaning compound.
- Will not etch glass or metal surfaces.
- Gel-like consistency controls dripping. Material "clings" to vertical surfaces.
- Low-odor and non-fuming – Ideal for interior application.

Limitations

- May dull or remove waxes or other applied finishes.
- Not intended for use on black marble.

REGULATORY COMPLIANCE

VOC Compliance

Stand Off® Liquid Marble Cleaner is compliant with all national, state and district VOC regulations.

TYPICAL TECHNICAL DATA

FORM	Blue colored gel
SPECIFIC GRAVITY	1.12
pH	9.0 – 10.0
WT/GAL	9.32 lbs
ACTIVE CONTENT	Not applicable
TOTAL SOLIDS	Not applicable
VOC CONTENT	Not applicable
FLASH POINT	126°F (52°C) ASTM D 3278
FREEZE POINT	21°F (-6°C) ASTM D 1177
SHELF LIFE	2 years in tightly sealed, unopened container

Liquid Marble Cleaner

PREPARATION

Protect people, vehicles, property and all non masonry surfaces from product, splash, residue, fumes and wind drift.

Protect plants and painted surfaces with polyethylene or other proven protective material.

Surface and Air Temperatures

Cleaning when temperatures are below freezing or will be overnight may harm masonry. Best cleaning results are obtained when air and masonry surface temperatures are 40°F (4°C) or above. If freezing conditions have existed, let masonry thaw and warm.

Equipment

Apply with a soft-bristled brush. Spray application is normally not suitable. Rinse with a sponge or pressure-rinsing equipment.

Storage and Handling

Store in a cool, dry place with adequate ventilation. Keep tightly closed when not dispensing. Published shelf life assumes upright storage of factory-sealed containers in a dry place. Maintain temperature of 45–100°F (7–38°C). Do not double stack pallets. Dispose of unused product and container in accordance with local, state and federal regulations.

APPLICATION

Before use, read "Preparation" and "Safety Information."

ALWAYS TEST each type of surface before overall application. Test using the following application instructions. Let test dry thoroughly before inspection.

Dilution

Use in concentrate to remove heavy soiling. For light soiling, dilute with up to 3 parts water.

Coverage Rates

Coverage is in square feet/meters per gallon of concentrate. Always test.

- *Porous Surfaces:*
75–200 sq.ft. (7–19 sq.m.)
- *Semi-Porous Surfaces:*
75–200 sq.ft. (7–19 sq.m.)
- *Non-Porous Surfaces:*
75–200 sq.ft. (7–19 sq.m.)

ALWAYS TEST

ALWAYS TEST a small area of each surface to confirm suitability and desired results before starting overall application. Test with the same equipment, recommended surface preparation and application procedures planned for general application.

Application Instructions

1. Use a soft-bristled nylon brush to apply cleaner liberally to the marble surface.
2. Leave the cleaner on the surface for 15–20 minutes. Don't let the gel dry on the surface.
3. Rinse the surface thoroughly with fresh water using sponges or low-pressure rinsing. Change rinse water frequently. Thorough rinsing is extremely important to ensure all residues are removed from the surface.

Cleanup

Clean tools and equipment using fresh water.

Liquid Marble Cleaner

SAFETY INFORMATION

Stand Off® Liquid Marble Cleaner is a combustible cleaning product. Use appropriate safety equipment and job site controls during application. Read full label and MSDS for precautionary instructions before use.

First Aid

Ingestion: Contact a physician immediately.

Eye Contact: Rinse for 15 minutes; get medical attention.

Skin Contact: rinse for 15 minutes. Seek medical assistance as needed.

24 Hour Emergency Information:
INFOTRAC at 800-535-5053

WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

PROSOCO, Inc. warrants this product to be free from defects. **Where permitted by law, PROSOCO makes no other warranties with**

respect to this product, express or implied, **including without limitation the implied warranties of merchantability or fitness for particular purpose.** The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. PROSOCO's liability shall be limited in all events to supplying sufficient product to re-treat the specific areas to which defective product has been applied. Acceptance and use of this product absolves PROSOCO from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be modified or extended by representatives of PROSOCO, its distributors or dealers.

CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Call 800-255-4255 and ask for Customer Care - technical support.

Factory-trained representatives are established in principal cities throughout the continental United States. Call Customer Care at 800-255-4255, or visit our web site at www.prosoco.com, for the name of the Stand Off® representative in your area.

BEST PRACTICES

ALWAYS TEST for best coverage rates and to confirm results before overall application. Test using the application instructions included herein. Let the test area dry thoroughly before inspection.

Cleaning when temperatures are below freezing or will be overnight may harm masonry. If freezing conditions existed, allow masonry to thaw and warm before application.

When diluting Liquid Marble Cleaner, always pour cold water into an empty bucket first, then carefully add product concentrate. Never use hot water.

Never go it alone. If you have problems or questions, contact your local PROSOCO distributor or field representative. Or call PROSOCO technical Customer Care, toll-free at 800-255-4255.

STANDOFF®

Liquid Marble Cleaner

PRODUCT DATA SHEET

PROSOCO

SINCE 1939

THIS PAGE INTENTIONALLY BLANK